



Most commonly used Exflor's Standardex Pavers have set the standards for making any exterior surface look better and be functionally more useful. They are a cut above the rest in terms of quality of material used, strength & anti-skid properties, suitable for light to medium traffic areas.





Superex Pavers

With 80 mm & 100 mm thickness & M40 - M50 grade strengths, Exflor's Superex Pavers are truly the superior choice for heavy traffic areas. Their heavy duty performance & Superior anti - skid properties make them a preferred choice for creating new landmarks in the city.

■ As per is 15658:2006, minimum specification based on application is given below.



Used for Building premises, Landscapes, Public Garden/ Parks, Domestic Drives, Paths and Patios, Pedestrian Plazas, Shopping Complexes ramps, Car Parks, Office Driveways, Housing Colonies, Office Complexes, Rural Roads with low volume traffic, Beach Sites, Tourist Resorts Residential Roads etc.



80 mm thickness-M40 Grade

Iscapes, Public Used for City Streets, Small and Medium Market Roads, Low Volume Roads, Utility Cuts on Arterial Roads, Petrol Pumps, Industrial Approach Roads, Table Topsetc.



100 mm thickness-M50 Grade

Used for Bus Terminals, Roads, on Expansive Soils, Service Stations, Industrial Pavements etc. Container Terminals, Ports, Dock Yards, Mine Access Roads, Bulk Cargo Handling Areas, Airport Pavements, Port Trusts, Shipyardsetc.



602, Kamat Towers, Patto, Panaji-Goa. Tel.:8806665764, 0832-2437107 email: mail@exflor.com | www.exflor.com

North Goa and Karnataka: 07507773413

South Goa and Maharashtra: 09860092114